


SML-ME / 8 磁附式鎖模力感測儀

SML-ME / 8 Magnet Clamping Force Control Sensor



- 避免歌林柱斷裂
Avoid tie bar broken.
- 保持模具和機器的平行度
Keep mold and machine aligned
- 延長模具和軸襯壽命
Extend die and bushing life.
- 減少模具的磨損和噴料
Less mold wear and flashing.
- 可重覆使用
Repeatable setup from run to run.




帶 8 個感測器，對歌林柱進行彎曲補償自動測量。可以快速測試結果和直接顯示總鎖模力，1%精度。
With 8 sensors, the tie bar stretches in automatically measured bending compensated. This is for fastest results and direct total clamping force indication with 1% accuracy.

特 徵：

Characteristics :

- 用2個強力磁鐵，快速容易地安裝
Quick and easy mounting with 2 super magnets
- 2個感測器可進行彎曲補償測量
2 sensors for bending compensated measurement.
- 適合任何歌林柱直徑
Fit any tie bar diameter.
- 高解析度精度 ± 1%精度
High resolution, 1% accuracy.
- 直接的量測值讀數，不用計算或對照表，DM4DB 顯示器直接顯示 $\mu\epsilon$, kN 或 ton
Direct reading in $\mu\epsilon$, kN or ton without calculation or conversion list.



技術資料：

Technical Data:

應變片 strain gauge	350 Ω
量測範圍 Measuring range	$\pm 800 \mu\epsilon$
感測器靈敏度(1/2 電橋補償) Sensitivity of sensor (1/2 bridge compensated)	1.0 mV/V @ F.S.
量測值線性誤差 Linearity	< 0.5 %
總精度 Over all accuracy	$\pm 0.5 \% \text{ F.S.}$
重覆性 Repeatability	0.1% F.S.
遲滯現象 Hysteresis	0.1% F.S.
操作環境溫度範圍 Operating temperature range	+0...+60°C
感測器尺寸 Sensor dimension	88 x 31 x 30 (不含螺帽高度)
電源供應電壓 Power supply	110...220 VAC / 50-60Hz

SENSORMATE Technology Inc.

6f., No.5, Ln.83, Sec.1, Guangfu Rd., Sanchong Dist., New Taipei City 241, Taiwan

<http://www.sensormate.com> E-mail : sales@sensormate.com

TEL : +886 2 2999 5245 FAX : +886 2 2995 0782